

USB FAST CHARGER GaN PD 6 PORT 145W



Model TGR-USB-145W-6P



- Supports charging of up to 6 devices at the same time
- Latest GaN technology for ultra efficient charging in a small size with less heat
- Features a wide range 100-240vac input for World use
- Standard Fig 8 input socket
- Power Delivery PD 3.0 for ultra fast charging of your devices
- Features LCD display showing real time combined charging levels for all connected devices
- Dimensions:



The Tiger 145W 6 port USB Fast Charger combines 4 USB C ports and 2 USB A port to provide a comprehensive charging device, engineered using latest GaN technology for wide compatibility in an ultra compact, pocket sized footprint. Ideal for home or office use and perfect for traveling due to its small size, the unit has an industry standard 2 pin Fig 8 C8 socket for wide compatibility with a wide range of power cable.

This unit does not come with an AC cable included as standard so please order your cable as required. Some order codes are listed below for reference.

Below you can see an example nameplate showing full output information

145W Desktop Charging Station

Model:TGR-USB-145W-6P

Input:100-240V~ 50/60Hz 2.5A

USB-C1/C2/C3 PD Output: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A(100W Max) PPS: 3.3-21V=5A

USB-C4 PD Output: 5V=3A, 9V=2.22A, 12V=1.87A(20W Max) PPS: 3.3-11V=2A

USB-A1/A2 QC 3.0 Output: 5V=3A, 9V=2A, 12V=1.5A(18W Max)

A1+A2 Output: 5V=2A+5V=2A

C4+A1 Output: 5V=2A+5V=2A

C4+A1+A2 Output: 5V=2A+5V=2A+5V=2A

C1+C2 or C1+C3 or C2+C3 Output: 65W+45W

C1+C2+C3 Output: 65W+30W+20W

C1+C2+C3+C4 Output: 65W+30W+20W+20W

C1+C2+C3+A1/A2 Output: 65W+30W+20W+18W

C1+C2+C3+C4+A1+A2 Output: 65W+30W+20W+5V=2A+5V=2A+5V=2A

Total Output:145W Max

Made in China

WWW.TigerPowerSupplies.com

Henley-On-Thames, Oxfordshire, UK, RG9 1UY



Suggested compatible AC cables:

UK 1 Metre

UK 2 Metre

Euro 2 Metre

USA 2 Metre

Australian 2 Metre

CPC order code PL15562

CPC order code PL15829

CPP order code PL13324

CPC order code PL17768

CPC order code PL17762



GaN 145W 4C2A LED Display Desktop Adapter

Support: PPS/PD3.0/PD2.0/QC4.0+/QC4.0/QC3.0/QC2.0/PE1.0/AFC/FCP/SCP/ APPLE2.4/

BC1.2 Input: AC 100-240V~50/60Hz 2.5A Max

USB-C1/C2/C3: PD3.0 100W(PPS 3.1-11V/5A) 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A

USB-A1/A2: (QC3.0 18W) 5V/3A, 9V/2A, 12V/1.5A

C1+C2/C3: 65W+45W

C2+C3: 65W+45W

C1+C2+C3+C4: 65W+30W+20W+20W

C1+C2+C3+A1/A2: 65W+30W+20W+20W

C1+C2+C3+C4+A1+A2: 65W+30W+20W+10W+10W+10W

Total Output: 145W

Certificate: CE UKCA

Plug: US/EU/KR/UK/AU (No mains lead supplied as standard - please order cable separately)

Color: Black as standard (White case on request subject to lead time and availability)



TIGER POWER PRODUCTS – QUALITY & RELIABILITY